



Housing NO.	Dimensions (mm / in.)																	Bearing No.	Adapter Sleeve	Locating Ring		wt (kg)
	d	Da	g	a	b	c	h	W	L	e	u	v	s	d ₁	d ₂	J	F			Number	QTY	
SNU505	20	52	25	165	46	19	40	73	67	130	13	20	M10	31.5	39.5	7.5	5	1205K	H205	SR52×5	2	1.90
SNU506-605	25	62	32	185	52	22	50	88	77	150	13	22	M10	36.5	44.5	7.5	5	1206K	H206	SR62×8	2	2.20
SNU507-606	30	72	34	185	52	22	50	93	82	150	13	20	M10	46.5	54.5	7.5	5	1207K 22207K	H207 H307	SR72×8.5 SR72×5.5	2 2	2.40
SNU508-607	35	80	39	205	60	25	60	108	85	170	15	20	M12	51.5	59.5	7.5	5	1208K 22208K	H208 H308	SR80×10.5 SR80×8	2 2	3.20
SNU509	40	85	30	205	60	25	60	111	85	170	15	20	M12	56.5	64.5	8.5	5	1209K 22209K	H209 H309	SR85×5.5 SR85×7	2 1	3.50
SNU510-608	45	90	41	205	60	25	60	114	90	170	15	20	M12	62.0	70.5	8.5	5	1210K 22210K	H210 H310	SR90×10.5 SR90×9	2 2	3.85
SNU511-609	50	100	44	255	70	28	70	129	95	210	18	23	M16	67.0	75.5	8.5	5	1211K 22211K	H211 H311	SR100×11.5 SR100×9.5	2 2	5.20
SNU512-610	55	110	48	255	70	30	70	134	105	210	18	23	M16	72.0	80.5	8.5	5	1212K 22212K	H212 H312	SR110×13 SR110×10	2 2	6.70
SNU513-611	60	120	51	275	80	30	80	149	110	230	18	24	M16	77.0	85.5	8.5	5	1213K 22213K	H213 H313	SR120×14 SR120×10	2 2	7.90
SNU515-612	65	130	56	280	80	30	80	155	115	230	18	26	M16	87.0	95.5	8.5	5	1215K 22215K	H215 H315	SR130×15.5 SR130×12.5	2 2	7.70
SNU516-613	70	140	58	315	90	32	95	175	120	260	22	29	M20	92.5	101.0	10.5	5	1216K 22216K	H216 H316	SR140×16 SR140×12.5	2 2	11.0
SNU517	75	150	61	320	90	32	95	181	125	260	22	30	M20	97.5	106.0	10.5	5	1217K 22217K	H217 H317	SR150×16.5 SR150×12.5	2 2	12.7
SNU518-615	80	160	65	345	100	35	100	192	140	290	22	27	M20	102.5	111.0	10.5	5	1218K 22218K 23218K	H218 H318 H2318	SR160×17.5 SR160×12.5 SR160×12.5	2 2 1	14.8
SNU519-616	85	170	68	345	100	35	112	209	145	290	22	27	M20	131.0	141.0	11.5	6	1219K 22219K	H219 H319	SR170×18 SR170×12.5	2 2	15.5
SNU520-617	90	180	70	380	110	40	112	215	160	320	26	32	M24	137.5	147.5	11.5	6	1220K 22220K 23220K	H220 H320 H2320	SR180×18 SR180×12 SR180×9.7	2 2 2	18.4
SNU522-619	95	200	80	410	120	45	125	239	175	350	26	32	M24	147.5	157.5	11.5	6	1222K 22222K 23222K	H222 H322 H2322	SR200×21 SR200×13.5 SR200×10.2	2 2 1	24.8
SNU524-620	100	215	86	410	120	45	140	271	185	350	26	32	M24	157.5	167.5	11.5	6	22224K 23224K	H3124 H2324	SR215×14 SR215×10	2 1	32.2
SNU526	110	230	90	445	130	50	150	290	190	380	28	35	M24	167.5	177.5	13.0	6	22226K 23226K	H3126 H2326	SR230×13 SR230×10	2 1	39.8
SNU528	115	250	98	500	150	50	150	302	205	420	35	42	M30	177.5	187.5	13.0	6	22228K 23228K	H3128 H2328	SR250×15 SR250×10	2 1	48.8
SNU530	135	270	106	530	160	60	160	323	220	450	35	42	M30	192.5	202.5	13.5	6	22230K 23230K	H3130 H2330	SR270×16.5 SR270×10	2 1	56.5
SNU532	140	290	114	550	160	60	170	344	235	470	35	42	M30	202.5	212.5	13.5	6	22232K 23232K	H3132 H2332	SR290×17 SR290×10	2 1	63.5

NOTES: 1. Foot of standard housing SSN type is solid without mounting holes or can be precast as 2-bolt (with prefix T) or 4-bolt mounting holes (with prefix F). 2. Taconite seal will be supplied as optional for perfect arrangement in severe operating conditions to prevent contamination from fine abrasive dust. 3. ZF rubber seals can be supplied upon request.